



Foam Door (F)



Glass Door (G)



260L



360L

## TECHNICAL PARAMETERS

Model	DT-V50M (F/G)	DT-V70M (F/G)	DT-V95M (F/G)	DT-V130M (F/G)
External Size(W*D*H) mm	450*445*585	470*450*707	470*450*925	505*525*925
Internal Size(W*D*H) mm	355*320*415	367*300*525	367*300*725	385*356*737
Capacity	50L	70L	95L	130L
Temperature Range	2°C~8°C			
Temperature Accuracy	0.1°C			
Control System	Microprocessor Control, Large Screen LED Display			
Alarm	Audible and Visual Alarm-Standard:High and low temperature, Sensor failure Audible and Visual Alarm-Optional:Power failure, Door ajar.			
Refrigeration Type	Forced air refrigeration system			
Refrigerant	R134a/R600a, CFC Free			
Condenser & Evaporator	High efficiency air-cooled condenser, made of copper			
Decondensation	Manual			
Door	Foam/Glass			
Construction	Structure	Unibody design & Mono-assembly foaming (Rigid polyurethane insulation material)		
	Internal Material	HIPS blister tank		
	External Material	Cold-rolled steel coated with anti-bacteria powder coating		
Shelves	1 pc	2 pcs	3 pcs	3 pcs
Consumption	60W	70W	70W	90W
Power Supply	AC220V±10%, 50/60Hz AC110V±10%, 60Hz			
Optional	Auto decondensation, Lock of door.			
Package Size(W*D*H) mm	565*575*660	575*590*775	575*590*995	620*645*975
Gross Weight(kg)	26(F) / 31(G)	43(F) / 48(G)	53(F) / 58(G)	53(F) / 58(G)

## TECHNICAL PARAMETERS

Model	DT-V260M	DT-V360M
External Size(W*D*H) mm	540*635*1900	660*655*1980
Capacity	260L	360L
Temp. Range	2°C~8°C	
Temp. Accuracy	0.1°C	
Control System	Microprocessor Control, Large Screen LED Display	
Alarm	Audible and visual alarm for: High and low temperature, System & sensor failure, Door ajar, Power failure alarm, Low backup battery alarm.	
Refrigeration Type	Forced air refrigeration system	
Refrigerant	R134a, CFC Free	
Condenser & Evaporator	Bundy tube condenser	
Defrost	Frostless design	
Construction	Structure	Unibody design & mono-assembly foaming (Rigid polyurethane insulation material)
	Internal material	HIPS engineering plastics, abrasion and acid resistant
	External material	Cold-rolled steel coated with anti-bacteria powder
Shelves	Adjustable shelves made of high quality steel wire	
	4 pcs	5 pcs
Consumption	200W	350W
Power Supply	AC110/220V±10%, 50/60Hz	
Standard Accessory	LED lamp & shelves, USB, probe access port, door keys	
Package Size(W*D*H) mm	588*664*2027	708*720*2132
Gross Weight	87kg	116kg